

FLOWLINE II™


One-Piece Body Construction Single Bag Housing Assembly

Eaton's advanced engineering provides:

- Unique one-piece body design that eliminates the traditional body to bottom cap circumferential weld.
- Most cost effective solution to single bag vessel requirements.
- Rated at 150psi at 250°F for high performance at economical pricing.
- Unique internal body to basket seal to prevent bypass.
- FLOWLINE style cover design provides safe and reliable "no tools required" access for bag replacement.
- Displacement style cover prevents spills when opening the cover.

Potential Cost Savings

A 2" flanged FLOWLINE II SBV in 316SS is up to 28% less expensive than competitors' offerings.



Unique internal body to basket O-ring seal prevents bypass and is easy to maintain.



FLOWLINE II models come standard with sturdy adjustable legs.

EATON

Powering Business Worldwide

Specifications

- The FLOWLINE II is available as either #1 size or #2 size units.
- Choice of three different materials of construction, Carbon Steel, 304 Stainless Steel and 316 Stainless Steel.
- Available end connections: 2" NPT or 2" 150# RF flanged. The #2 size unit is also available with 3" 150# RF flanges in the side in/side out and loop configurations as well as bottom out configuration.
- Units come standard with a 316 stainless steel support basket.
- Kynar® compression ring provides an advanced, long-term solution for securing the filter media and support basket into the enclosure.
- Adjustable painted carbon steel mounting legs are included.
- Buna-N O-rings for the cover and basket seal. Viton or EPDM O-rings are optional.
- 1/4" NPT vent and gauge port connections on the cover. Additional 1/4" NPT gauge connections on the body are optional.
- The FLOWLINE II with 2" connections is available in three configurations: side in and bottom out, side in and side out on opposite sides for inline piping or side in and side out on the same side for loop design layouts or duplexing. These units come standard with 2" NPT bottom drain connections.
- Bead blast external finish is standard for stainless steel construction and shop paint is standard for carbon steel construction.



SPLASH GUARD option for added safety


- Helps protect operators from unexpected pressurized spray and discharge
- Reduces operator exposure to potentially hazardous material
- Provides additional eye and face protection

FLOWLINE II can be configured into MODULINE™ assemblies

- Higher efficiency & operation cost savings
- Modular flexibility for adding capacity
- Smaller footprint than duplexed multibag housings
- Continuous flow capability
- Capital cost savings of 30% to 40% or more



Filter Bags



Progaf

Up to 13 layers of media



Accugaf

Absolute rated at 99%



Lofclear

Oil removal and gels



Hayflow

Up to 5 times the life of standard bags



Durgaf

Up to 3 times the life of standard bags



Sentinel

High quality, durable performance



Unibag

Efficiency with an economical advantage

Eaton North America – HQ

70 Wood Avenue, South
2nd Floor
Iselin, NJ 08830

Toll Free: (800) 656-3344
(North America only)

Voice: (732) 767-4200
Fax: (952) 906-3706

Eaton Europe/Africa/Middle East

Auf der Heide 2
53947 Nettersheim
Germany

Voice: +49-2486-809-0
Fax: +49-2486-809-800

Eaton Brazil

Av. Julia Gaioli, 450 –
Bonsucesso
07250-270 – Guarulhos
Brazil

Voice: +55 (11) 6465-8780
Fax: +55 (11) 6480-2808

Eaton China

No.3, Lane 280, Linhong Road
Changning District, 200335
Shanghai, P.R. China

Voice: 86-21-5200-0099
Fax: 86-21-5200-0400

Eaton Singapore

4 Loyang Lane #04-01/02
Singapore 508914

Voice: +65 68251668
Fax: +65 68251639

©2009 Eaton Corporation. All Rights Reserved.
All trademarks and registered trademarks are the property of their respective owners. Litho USA

For more information,
please e-mail us at
filtrationinfo@eaton.com
or call 732-767-4200.

Visit us online at
filtration.eaton.com for
a complete list of Eaton's
filtration products.

All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.



Powering Business Worldwide